# CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC4-15W-MCT-SA-D CRLC4-15W-MCT-SA-D-WH

4" LED COMMERCIAL SQUARE & WALL WASH RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

#### **Customer Name:**

Project Name:

Note: Type:



6 1/4"(H) X 4" (W)

## -eatures

- 4" Haze & White Finish TRIM
- MCT: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

# **Technical Specifications**

#### **Electrical:**

Voltage: 120-277VAC 50/60Hz

Wattage: 15W Power factor: >0.90 Efficacy: 85 LPW

### Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

## Lighting:

- MCT: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 1275LM
- Color temperature: 3000K/4000K/5000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

## **Applications:**

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

#### Other Models:

- 20W | 1720LM | CRLC4-20W-MCT-SA-D
- 20W | 1720LM | CRLC4-20W-MCT-SA-D-WH













## Photometrics: CRLC4-15W-MCT-SA-D





20 15 10 5 2fc 1fc 0.5fc 0.1fc o 10 25

BUG Rating: B1-U1-G0

15W 5000K, Area 25" x 25' Mounting Height: 9'

## **Other Views:**











CRLC-EGN-15W-MCT-D

CRLC-TRM-4SA

CRLC4-15W-MCT-SA-D

White









CRLC-TRM-4SA-WH



CRLC4-15W-MCT-SA-D-WH

### Performance Table: CRLC4-15W-MCT-SA-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-15W-MCT-SA-D	15W	120-277V	1275LM	3000K 4000K 5000K	B1-U1-G0	85
CRLC4-15W-MCT-SA-D-WH						

# Sample Ordering

**Shape Dimming Housing** Model Watt CRLC4 | = |15W| = |MCT| = | SA | Blank

## WH = WHITE

### **Factory-Installed Option:**



## **Factory-Installed Option:**

Blank = No Option For Accessories OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

### **Example:**

1. CRLC4-15W-MCT-SA-D

(FOR 15W CRLC4 MCT 120-277V)

1. CRLC4-15W-MCT-SA-D OPT-EM-HB1EXT

(FOR 15W CRLC4 MCT 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)





