LDSW SERIES OUTDOOR LIGHTING

LDSS-MCT5-SIL








LED outdoor wall light with aluminum housing & powder-coated finish, acrylic diffuser. Ideal for general site lighting, residential buildings, doorway, pathway and parking areas.

Customer Name:

Project Name:

Note: Type:



Features

- Silver Finish
- 7-Year Warranty

- Multi CCT (Selectable Switch on the LED Board)
- Aluminum Housing and Steel Back Plate
- Rated life: 70,000 Hrs

Technical Specifications

Electrical:

Voltage: 120V AC 50/60Hz
Power Factor: >0.90
Wattage: 12W
Efficacy: 100 LPW

Total Harmonic Distortion: ≤20 %

Lighting:

- Multi CCT (Selectable Switch on the LED Board)
- Lens: Acrylic PC lensTotal Lumens: 1200LM
- Color Temperatures: 2700K/3000K/3500K/4000K/5000K
- Color Rendering Index: CRI ≥ 80

Beam Angle: 120°
Rated life: 70,000 Hrs

Mechanical:

- Aluminum Housing and Steel Back Plate
- Silver Finish
- Maximum Ambient Temperature: 50~113°F
- IP42, Suitable for outdoor use
- 7-Year Warranty

Applications:

 LED outdoor wall light with aluminum housing & powder-coated finish, acrylic diffuser. Ideal for general site lighting, residential buildings, doorway, pathway and parking areas.

Other Models:

• 12W | 1200LM | LDSW-MCT5-ORB











Photometrics: LDSW-MCT5-SIL





0.1fc 0.1fc 0.20 12W, 5000K, Area 20'x 20' Mounting Height: 9'

BUG Rating: B0-U3-G1

Other Views:







Front View



Back View

Performance Table: LDSW-MCT5-SIL

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LDSW-MCT5-SIL	12W	120V	1200LM	2700K/3000K/3500K/4000K/5000K	B0-U3-G1	100

Sample Ordering

Model Color Temp. Finish

LDSW - MCT5 - SIL

Example:

1. LDSW-MCT5-SIL

(FOR LDSW 12W MCT5 FIXTURE 120V)

Performance Table: LDSW-MCT5-ORB



Bottom View



Front View



Back View



