
# LSS SERIES Commercial Lighting





Ideal choice for residential, commercial, and industrial lighting. Steady performance and long lifetime. Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below



Customer Name:	
Project Name:	
Note:	Туре:



44 1/2"(L) x 2 3/5"(W) x 2 3/4"(H)

## **Features**

- High Lumen Efficienc
- Ceiling Mount or Suspended Mount

- Linkable (Optional Alignment Bracket Available)
- Multi Color Temperature & Multi Power (Selectable Switch Inside Fixture)

# **Technical Specification**

#### **Electrical:**

Voltage: 120-277VAC 60HzWattage: 29W/ 34W/ 39W/ 46W

Power Factor: >0.99Efficacy: 130 LPW

#### Mechanical:

- Black Finish
- High Lumen Efficiency Lumen
- Lens: Polycarbonate Frosted Lens, Shatter Resistant
- Ceiling Mount or Suspended Mount
- Operating Temperature: -4°F to 122°F
- Housing: Cold-rolled Steel
- IP20, Indoor Use Only
- 5-Year Warranty

## Lighting:

- Dimmable: 0~10V Dimming
- Total Lumens: 5980LM
- Color Temperatures: 3500K/ 4000K/ 5000K
- Multi CCT & Multi Power (Selectable switch inside fixture)
- Color Rendering Index: CRI ≥ 80
- Reduces Energy Consumption Up to 80% Compared to a Fluorescent Fixture
- Rated life: 50.000 Hrs

### **Applications:**

- LED Strip Light is a cost-effective, energy-efficien lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.
- Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below
- Ideal for residential, commercial, and industrial lighting. Steady performance and long lifetime

#### Other Models:

34W | 4420LM | LSS-4FT-34W-MCTP

46W | 5980LM | LSS-4FT-46W-MCTP













#### Photometrics: LSS-4FT-46W-MCTP





#### **Other Views:**





**Back View** 

Side View

Performance Table: LSS-4FT-46W-MCTP-BK

MODEL NO.	Wattage	Voltage Lumens		Color Temp.	BUG Rating	LPW
LSS-4FT-46W-MCTP-BK	29W 34W 39W 46W	120~277V	5980LM	3500K 4000K 5000K	B2-U3-G2	130

## Sample Ordering

Model	Size	Wattage	e Co	lor Ten	ıp.	Housin	g
LSS	4FT	46W	_ [	ИСТР		BK	7

#### **Accessories:**

Blank = No Option For Accessories

LSS-CB2-BK = ALIGNMENT BRACKET BLACK FINISH

SCL-TBC-WN = T-BAR CLIP WITH SUSPENSION HOLE ON TOP. WING NUT AND WASHER INCL. SCL-CSY = ADJUSTABLE 1/16" 6FT. SUSPENSION KIT WITH Y-CONNECTOR KEY HOLE SET + 2 T-BAR CLIPS + 1 CABLE BUSHING + 3 PLASTIC TIE STRAPS - 70 LBS. MAX LOAD

SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 1/16" 10FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY20 = HEAVY-DUTY ADJUSTABLE 1/16" 20FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY110 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

SCL-GSY120 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

### **Factory-Installed Options:**

Blank = No Option For Accessories

OPT-EM-CM1INT= INTERNAL EMERGENCY BACKUP BATTERY
OPT-SEN-2MDR-36= PROGRAMMABLE MICROWAVE BI-LEVEL
OPT-HBC-125TL-BK = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V
OPT-HBC-277TL-BK = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V

OPT-HBC-125SB-BK = STRAIGHT BLADE PLUG 10FT, 15A,125V, 3-CONDUCTOR 18AWG WEC-3RC = OPTIONAL REMOTE

#### **Example:**

1. LSS-4FT-46W-MCTP-BK

(FOR LSS 46W MCTP FIXTURE 120-277V)

2. LSS-4FT-46W-MCTP-BK LSS-CB2 (FOR LSS 46W MCTP FIXTURE 120-277V) (ALIGNMENT BRACKET)

3. LSS-4FT-46W-MCTP-BK LSS-CB2 OPT-EM-CM1INT (FOR LSS 46W MCTP FIXTURE 120-277V)
(ALIGNMENT BRACKET)
(INTERNAL EMERGENCY BACKUP BATTERY)

#### ACCESSORIES:



-



SCL-GSY110 SCL-GSY120 SC

SCL-TBC-WN

ALIGNMENT (COUPLING)
BRACKET
(Can be painted)



大大

SCL-CSY

SCL-GSY10 SCL-GSY20

## FACTORY-INSTALLED OPTIONS:







OPT-HBC-125SB-BK

OPT-HBC-125TL-BK

OPT-HBC-277TL-BK







OPT-EM-CM1INT

OPT-SEN-2MDR-36

WEC-3RC

