RDP SERIES LED Retrofit Trims


RDPS6-MCTP








LED retrofit trims have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.





8 1/2" x 3 1/5"

Features

- 6" Smooth Recessed Trim
- Multi CCT and Power (Selectable Switch on the Back of the driver)
- 5-Year Warranty
- Composite Polycarbonate
- JA8-E-2019 & Title 24 Compliant (approved by the state of California and registered with the California Energy Commissions (CEC)

Technical Specifications

Electrical:

Voltage: 120V ACPower Factor: >0.90Wattage: 17W/13W/10W

Efficacy: 80 LPW

Total Harmonic Distortion: ≤15 %

Mechanical:

- Composite Polycarbonate, White Finish
- Maximum Ambient Temperature: 104°F
- Includes 8" Medium Base E-26 Screw-in Adapter That Fits any Standard Incandescent Down-light
- White Translucent Acrylic Lens
- Fits in Standard and Shallow 5" & 6" Recessed Housings
- Wet Location, O-Ring pre-installed in fixture
- White Finish
- 5-Year Warranty

Lighting:

- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- Multi CCT and Power (Selectable Switch on the Back of the driver)
- Total Lumens: 1360LM Max.
- Color Temperatures:

2700K/3000K/3500K/4000K/5000K

- Color Rendering Index: CRI ≥ 90
- Rated life: 50,000 hrs

Applications:

 LED retrofit trim have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

Other Models:

• 13W | 1040LM | RDPS4-MCTP















Photometrics: RDPS6-MCTP





BUG Rating: B1-U2-G1

30 20 15 10 2fc 1fc 0.5fc 0.1fc 15

Simulation Based on 2700K Area 30'x 30' Mounting Height: 9'

Other Views:







Side View Front View **Back View**

Performance Table: RDPS6-MCTP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
RDPS6-MCTP	10W	120V	800	2700K/ 3000K/ 3500K/ 4000K/ 5000K	B0-U2-G1	80
	13W		1040			
	17W		1360			

Compatible Dimmer List:

MODEL NO.	BRAND	MODEL NO.	BRAND	MODEL NO.	BRAND
CTCL-153PDH-WH	LUTRON	DW6HD-1BZ	LEVITON	RHCL453PW	LEGRAND
DVCL-153P-WH	LUTRON	LIGH ALMOND NO.6672 600W	LEVITON		
DVCL-153PR-WH	LUTRON	WHITE NO.IPL06 600W	LEVITON		
MACL-153M-WH	LUTRON	WHITE NO.6674 600W	LEVITON		
MACL-153MH-WH	LUTRON				

Sample Ordering

Model Color Temp.

RDPS6 -MCTP

Accessory:

Blank = No Option For Accessories E26-CONVERTER = SCREW-IN ADAPTER THAT FITS ANY STANDARD

Factory-Installed Option:

Blank = No Option For Accessories OPT-EM-DL1EXT = EXTERNAL BATTERY BACKUP

Example:

1. RDPS6-MCTP

(FOR RDPS6 13W MCTP FIXTURE 120V)

2. RDPS6-MCTP (FOR RDPS6 13W MCTP FIXTURE 120V) OPT-EM-DL1EXT (EXTERNAL BATTERY BACKUP)

ACCESSORY:



E26-CONVERTER Includes Medium Base E-26 Screw-in Adapter That Fits Any

FACTORY-INSTALLED OPTION:



OPT-EM-DL1EXT EXTERNAL BATTERY BACKUP

