

# RSL SERIES RESIDENTIAL LIGHTING



RSL10-MCT5  
LED ULTRA SLIM RECESSED LIGHTS

Customer Name: \_\_\_\_\_

Project Name: \_\_\_\_\_

Note: \_\_\_\_\_

Type: \_\_\_\_\_



8 19/32" x 7 9/16"

LED DOWNLIGHTS (SMOOTH TRIM) - 10" ROUND Ideal for New As Well As Old Residential And Commercial Constructions.

## Features

- 10" Smooth Recessed Trim
- Multi CCT (Selectable Switch on the Back of the driver)
- Isolated Driver for Improved Thermal Management
- 5-Year Warranty
- Spun Aluminum with White Powder Coat Finish

## Technical Specifications

### Electrical:

- Voltage: 120V AC
- Output Voltage: 36VDC
- Power Factor: >0.90
- Wattage: 20W
- Efficacy: 75 LPW
- Total Harmonic Distortion: ≤15 %

### Mechanical:

- 1/4" Thick
- Up to 9 AWG18 Wires
- Die-cast Aluminum with white powder coat finish
- Pot Light Housing is Not Required Even for Insulated Ceiling
- Junction box 1" Thick Included with Fixture
- Typel Crated: Approved for direct contact with insulation
- Maximum Ambient Temperature: -40°F to 104°F
- Damp Location

### Lighting:

- Dimming: Dimmable Down to 10% Using a Standard TRIAC LED Dimmer
- Lens: 0.125" White Translucent Acrylic
- Can Rotate after Installation to Align
- LED: Seoul DOB (Driver On Board) Technology
- Optics: White Translucent Acrylic
- Total Lumens: 1500LM
- Color Temperatures: 2700K/ 3000K/ 3500K/ 4000K/ 5000K
- Multi CCT (Selectable Switch on the Back of the driver)
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 100°-110°
- Rated life: 50,000 hrs

### Applications:


- LED recessed trims have been designed to be a flexible lighting solution for new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

### Other Models:


• 6W | 400LM | RSL3-MCT5 • 9W | 630LM | RSL4-MCT5 • 15W | 1125LM | RDL6-MCT5 • 18W | 1350LM | RSL8-MCT5 • 24W | 1800LM | RSL12-MCT5



## Photometrics: RSL10-MCT5




BUG Rating: B1-U2-G1



## Other Views:



Side View



Front View



Junction box 1-1/4" thick included with fixtures

Back View

## Performance Table: RSL10-MCT5

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
RSL10-MCT5	20W	120V	1500LM	2700K	B1-U2-G1	75
				3000K		
				3500K		
				4000K		
				5000K		

## Sample Ordering

Model      Color Temp.

RSL10      -      MCT5

### Accessories:

Blank = No Option For Accessories  
 RSL-EXT-10FT-MCT = 10 FT. EXTENSION CABLE FOR USE WITH ALL SLIM LIGHT  
 RSL10-GR = GOOF RING FOR 10IN LIGHTS WITH BUTTERFLY WINGS  
 E26-CONVERTER = SCREW-IN ADAPTER THAT FITS ANY STANDARD

### Factory-Installed Option:

Blank = No Option For Accessories  
 OPT-EM-DL1EXT = EXTERNAL BATTERY BACKUP

### ACCESSORIES:



**E26-CONVERTER**  
 Includes Medium Base E-26  
 Screw-in Adapter That Fits Any  
 Standard



**RSL-EXT-10FT-MCT**  
 10 Ft. Extension Cable For use  
 with all Slim Light



**RSL10-GR**  
 Goof Ring For 10in Lights With Butterfly Wings

### FACTORY-INSTALLED OPTION:



**OPT-EM-DL1EXT**  
 EXTERNAL BATTERY BACKUP

## Example:

- RSL10-MCT5 (FOR RSL10 20W MCT5 FIXTURE 120V)
- RSL10-MCT5 (FOR RSL10 20W MCT5 FIXTURE 120V)  
 OPT-EM-DL1EXT (EXTERNAL BATTERY BACKUP)



## Compatible Dimmer List:

MODEL NO.	BRAND
6631-1LT	LEVITON
MACL-153MLH-AL	LUTRON
TGCL-153PH-LA	LUTRON
DVW-603PGH-WH	LUTRON
CT-600PR-WH	LUTRON
LGCL-153PHL-IV	LUTRON
TGCL-153PH-LA	LUTRON
LSLV603PWV	LUTRON
6674-POW	LEVITON
DVCL-153P	LUTRON
MSCL-OP153P	LUTRON
CTCL-153P	LUTRON
MACL-153M	LUTRON
HCL453PTCCCV6	PASS & SEYMOUR
LSLV603PWV	PASS & SEYMOUR

