SFX SERIES OUTDOOR LIGHTING

SFX-G7-200-500W-45D-50K


GENERATION 7 STADIUM LIGHT




Ideal for Stadium lighting, Sports fields, parking lots, docks railway and container yards, Architectural lighting, Industrial and commercial exterior lighting, trade shows, exhibitions



Customer Name: Project Name: Note: Type:





25 3/4"(H) x 22"(W) x 20"(D)

eatures

- Die-Cast Aluminum Housing with Powder Coat Finish (Black)
- 7-year Warranty
- 20KV Lightning Surge Protection

Technical Specifications

Electrical:

Voltage: 120-277V AC 60Hz

Wattage: 500W

Power Factor: >0.90~0.97

Efficacy: 150LPW

Mechanical:

- Die-Cast Aluminum Housing with Powder Coat Finish (Black)
- Cord type: 3' SJTW 18/3 AWG Cable
- Half Shroud & U Mounting Bracket Included
- Effective Projected Area (EPA): 1.8 (sq. ft.)
- Operating Temperature: -40°F to 176°F
- IP Rating: IP65, Suitable for Wet Locations
- 7-year Warranty

Lighting:

20KV Lightning Surge Protection

Total lumens: 75000LM Color Temperatures: 5000K

Color Rendering Index: CRI ≥ 70

Rated Life: 70,000 Hrs Beam Angle: 45°

Applications:

Stadium lighting, Sports fields, parking lots, docks, railway and container yards, Architectural lighting, Industrial and commercial exterior lighting, trade shows, exhibitions.

1000W | 150000LM | SFX-G7-700-1000W-45D-50K













Photometrics: SFX-G7-200-500W-45D-50K



BUG Rating: B5-U4-G2



Other Views:



Shown with shroud



Sidev View



Back View

Performance Table: SFX-G7-200-500W-45D-50K

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
SFX-G7-200-500W-45D-50K	200W 300W 400W 500W	120~277V	30000LM 45000LM 60000LM 75000LM	5000K	B5-U4-G2	150

Sample Ordering

Model	Style	Min. Watt	Max. Watt	Beam Angle	Color Temp).
SFX =	G7	- 200 -	600W –	45D	= 50K	

Accessory:

Blank = No Option For Accessories SFX-G7-SF = Slip Fitter Adapter

Accessory:



SFX-G7-SF

Other Model: SFX-G7-700-1000W-45D-50K



Shown with shroud



Side View



Back View



