SFX SERIES OUTDOOR LIGHTING

SFX-G9-600W-30D-50K

LED STADIUM FLOOD LIGHTS







Ideal for Stadium lighting, Sports fields, parking lots, docks railway and container yards, Architectural lighting, Industrial and commercial exterior lighting, trade shows, exhibitions

Customer Name:

Project Name:

Note: Type:





18 1/3"(H) x 17 4/5"(W) x 21"(D)

Features

- Die-Cast Aluminum Housing with Powder Coat Finish (Black)
- LED: Lumileds Luxeon SMD 5050

- 7-year Warranty
- Lens: Prismatic Polycarbonate Lens

Technical Specifications

Electrical:

Voltage: 120-277V AC 60Hz

Wattage: 600W

Power Factor: >0.90~0.97

Efficacy: 150LPW

Mechanical:

- Die-Cast Aluminum Housing with Powder Coat Finish (Black)
- Cord type: 3' SJTW 18/3 AWG Cable
- Effective Projected Area (EPA): 1.8 (sq. ft.)
- Operating Temperature: -40°F to 176°F
- IP Rating: IP65, Suitable for Wet Locations
- 7-year Warranty

Lighting:

Selection:

Lens: Prismatic Polycarbonate Lens

LED: Lumileds Luxeon SMD 5050

Total lumens: 90000LM

Color Temperatures: 5000K

Color Rendering Index: CRI ≥ 70

Rated Life: 70,000 Hrs

Beam Angle: 30°

Applications:

 Stadium lighting, Sports fields, parking lots, docks, railway and container yards, Architectural lighting, Industrial and commercial exterior lighting, trade shows, exhibitions.

1000W | 150000LM | SFX-G9-1000W-30D-50K










Photometrics: SFX-G9-600W-30D-50K



25 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 600W 5000K, Area 80'x 80' Mounting Height: 9'

Other Views:







Front View



Back View

Performance Table: SFX-G9-600W-30D-50K

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
SFX-G9-600W-30D-50K	600W	120~277V	90000LM	5000K	B5-U0-G2	150

Sample Ordering

Model		Style		Watt		Size	Co	Color Temp.		
	SFX	G9		600W	_	30D	_	50K	7	

Accessories:

Blank = No Option For Accessories SFX-G9-SH1= SHROUD FOR G9 600W STADIUM LIG SFX-G9-SF= SLIP FITTER, COMES WITH ITS OWN REPLACEMENT "U" BRACKET

ACCESSORIES:







SFX-G9-SF

Example:

- 1. SFX-G9-600W-30D-50K
- SFX-G9-600W-30D-50K SFX-G9-SH1

(FOR SFX 600W 50K FIXTURE 120-277V)

(FOR SFX 600W 50K FIXTURE 120-277V) (SHROUD FOR 600W)



