SOLS SERIES


Outdoor Lighting

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

SOLS-1FT-MCT


SOLAR SIGN AND BILI BOARD LIGHTS


Multi Color Temperature (Selectable)



Ideal for general site lighting, alleys, loading docks, doorway, pathway, and parking areas.







4 3/5"(H) X 11 4/5"(W)

Features

- 7-Year Warranty
- Robust Aluminum Alloy + Polycarbonate Cover
- Lifespan: 70000 Hrs.
- Lens: TYPE III Optic Lens

Technical Specifications

Electrical:

LED Wattage: 5WPower Factor: 0.95

Efficacy: 100 LM/W

Mechanical:


- Robust Aluminum Alloy + Polycarbonate Cover
- Operating Temperature: 14°F to 122°F
- IP Rating: IP65

Lighting:

- Lens: TYPE III Optic Lens
- LED: Lumileds Luxeon 5050
- Total Lumens: 500LM
- Color Temperature: 3000K/6000K
- Color Rendering Index: >70
- Lifespan: 70000 Hrs.

Applications:

· Ideal for Ideal for doorway, pathway and alleys



Working mode: Dusk to Dawn Full Brightness for First 5Hrs. Dim to 25% for 7Hrs.

Battery:

- Operation on Full Charge: 6-8 hrs. Depending on the Sunlight Quality, See The Map On Page 3
- Battery Type: Lithium-ion 5200mAh
- Battery Life: More than 2000 Cycles (2000/365 days = 5.47 years) With Overcharge And Over-Discharge Protection

Other Model:


• 10W | 1000LM | SOLS-2FT-60K


• 20W | 2000LM | SOLS-4FT-60K






Photometrics: SOLS-1FT-MCT








BUG Rating: B1-U2-G0

Area 35'x 55' Mounting Height: 9'

Other Views:







Side View

Front View

Back View

Performance Table: SOLS-1FT-MCT

MODEL NO.	LED WATTS	Lumens	Color Temp.	BUG Rating	LPW
SOLS-1FT-MCT	5W	500LM	3000K 6000K	B1-U2-G0	100

Sample Ordering

Model Size Color Temp. SOLS 1FT MCT



Average Daily Solar Radiation Per Month:

Increasing the tilt 15° in the winter or decreasing 15° in the summer gives the maximum sunlight for recharging the battery.

