



eLucent MINI WALL PACK



- **DLC-Listed**
- **Luminous Efficacy of 105 lm/W or Higher**
- **IP65 Rated**

ATG's Mini Wall Pack offers the superior light quality of our larger eLucent Wall Packs in a more space-conscious form factor. The rich bronze finish complements building exteriors, landscapes, entryways, walkways, and facades. The luminaire is available in a range of color temperatures for wall-washing, perimeter, and security lighting. Mini Wall Pack fixtures are IP65 rated and tested for use in wet locations.

OPTICS

The compact fixture delivers virtually the same level of light output as a full size wallpack. Color rendering, at CRI of 80+, is improved over full size wallpacks. This creates more accurate visibility when the Mini Wall Pack is the sole source of light, a feature highly desirable for safe foot traffic. CCT is available in 4000K and 5000K, optimized for security and night visibility.

CONSTRUCTION

The eLucent Mini Wall Pack is precision-manufactured from heavy-wall, die-cast aluminum. Thermal management is integral to the design and our heat sinks facilitate excellent thermal transfer, including at temperatures over 40°C. The luminaire is tested for use in wet locations. It is equipped with a silicone gasket to prohibit the access of dust and sprays of water, as well as the prevention of corrosion, water damage, dust and insect infiltration.

ELECTRICAL

Luminaire lifespan is 60,000 hours, or over 13 years at 12 hours operation per day. Standard input voltage is 120-277V, and 347-480V drivers are available on all units. Luminous efficacy is 105 lm/W.

MOUNTING

Convenient, modular design means the eLucent Mini Wall Pack may be mounted to nearly any vertical surface for secure, reliable, illumination. The easy-to-install luminaire is packaged ready for standard junction boxes, requiring no additional modifications to install.

STANDARD FEATURES

OPTIONS

FINISH

Sample Order: WPMN20-4K-G2

SERIES	WATTAGE	CCT	VOLTAGE	DIMMING	GENERATION	OPTIONS
WPMN=Mini Wall Pack	20= 20W 40=40W	-4K=4000K -5K=5000K	Blank=100-277VAC	Blank=1-10V Dimming -ND=Non-Dimming	-G2=Generation 2	LOD=Bi-Level Sensor MPC=On/Off Sensor EKS=Photocell Sensor EM=Emergency Backup Battery

Performance Data

PART NO.	WATTS(W)	INPUT VOLTAGE(VAC)	EFFICACY(Lm/W)	LUMENS(Lm)	CRI	CCT (K)	PF	THD	L70 (Hours)	DIMENSIONS (L*W*H)(Inches)
WPMN20	20.3	120-277	105	2100	80+	5000	>0.9	<20%	60,000	9.25*7.28*3.84
WPMN40	39.2	120-277	92.5	3700	80+	5000	>0.9	<20%	60,000	9.25*7.28*3.84
COLOR	HOUSING	LENS TYPE	CERTIFICATION	WARRANTY	*Not all versions of this product may be DLC-qualified. Please inquire with our sales team.					
Bronze	Die Cast Aluminum	Clear Glass	DLC, ETL	10 Years						

