

ϕ 3.00 OD
 ϕ 2.76 ID

16.13
 13.13 TYP

ϕ 2.38 OD
 ϕ 2.14 ID

3" Standard
 Round Pole Cap

ϕ 1.00 ID
 Conduit Hole
 (3 Places)


Hex Head Screw
 Black Oxide
 M8 x 1.25 Thread, 25mm
 3 Places 120 Apart

90° TYP

29.25

All dimensions and specifications are subject to change without any notice.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF *Energy Light, Inc.* ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF *Energy Light, Inc.* IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN INCHES		DRAWN	MKA
		TOLERANCES:		ENG APPR.	
		FRACTIONAL \pm 1/64		MFG APPR.	
		ANGULAR: \pm 0.5°		Q.A.	
		TWO PLACE DECIMAL \pm 0.01			
		THREE PLACE DECIMAL \pm 0.005			
		INTERPRET GEOMETRIC TOLERANCING PER:		 Energy Light, Inc. 1881 Rose Road Lake Zurich, IL 60047	
		MATERIAL			
		STEEL			
NEXT ASSY	USED ON	FINISH			
APPLICATION		DO NOT SCALE DRAWING			

TITLE:
**Spoke Bracket
 with 3 Arms
 at 90°**

SIZE	ITEM NO.	REV
B	PTB390	
SCALE: 1:4	WEIGHT: 11.5 lbs	SHEET 1 OF 1