

Puck Lighting
RACUS2




Puck Lighting
RACUS2



Puck Lighting

RACUS2



- Plug & play (External power supply)
- Ultra-thin design with 4/16" (6mm) in thickness
- Easy installation option
- Lifetime: 50,000hrs (ta=95°F, 35°C)
- Ta: -4°F-95°F (-20°C-35°C)
- Material: PC



Dimensions: (inches/mm)



How to order using our catalog numbers:
Example: RACUS2-330K110WSM

Series	Diameter	Color Temp	Beam Angle	Finish	Installation
RACUS2	3 - 2.6"(65mm)	30K - 3000K 40K - 4000K	110 - 110°	W - White	SM - Surface Mounting

Catalog No.	Model	Description					Max. Pcs Per LED Power Supply 30W (NA159-3024FA-12A6)
		Rated Input	Ra	Wattage	Luminous Flux (TYP@4000K)	Included	
RACUS2-330K110WSM	RACUS2-R7-24V	24VDC	85	2W	140lm	1pc LED fixture 1pc double-sided adhesive tape 1pc mounting clip	12 pcs
RACUS2-340K110WSM							

How to choose your driver & cables:

Catalog No.	Description	Photo
NA159-3024FA-12A6	Model: SLT30-24VF-A Input: 100-120VAC NA plug 1 + 59" cable. Output: 24VDC 12-way splitter JB-12A + 6" cable.	

*Note: For alternative driver configurations, please contact our sales department.


Puck Lighting

RACUS2

Vertical & Horizontal Beamwidth			Center Beam FC
	110°		4000K
12"		34-1/4"	68
18"		51-7/16"	30
24"		68-9/16"	17
30"		85-11/16"	11
H		D	140 lm

Installation

Mounting clip installation



Double-sided adhesive tape installation

