

SPIRIT PANEL 2X4 LED

Architectural Indoor



PROJECT:

TYPE:

PO#:

QTY:

COMMENTS:




FEATURES

- 0-10V Dimmable
- 120 Degree Beam Angle
- 5 Year Warranty
- Aluminum Frame In White Finish, Steel Die-Formed Back Enclosure
- cULus Listed Damp Location For Ceiling Mount
- DLC Approved
- IC Rated For Insulated Ceilings
- Integral Earthquake Clips for Secure Attachment
- LED Backlit Flat Panel
- Linear Driver Integrated Into Side of Panel
- Operating Temp Range -20 Degrees C to 35 Degrees C
- PMMA Lenses Over LEDs, PS Diffuser
- Remote Battery Available
- RoHS, FCC
- Surface Mount and Suspension Mount Cable Kit Accessories Available
- Weight: 8.82 lbs

LINE DRAWING

LINE DRAWING NOT TO SCALE



FINISHES

Matte White



SPIRIT PANEL 2X4 LED

Architectural Indoor



Fixture Core

PROJECT:

TYPE:

PO#:

QTY:

COMMENTS:

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
FPE2X4-P - Flat Panel 2' x 4'	L40.0-ZE - 40.0W 0-10V Dimming Driver L50.0-ZE - 50.0W 0-10V Dimming Driver	120V - 277V	0-10V Dimming
ORDER INFO			
FPE2X4 Example ^	L40.0-ZE	120-277V	

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	MW - Matte White (Standard)	35K - 3500K Color Temp. 40K - 4000K Color Temp. 50K - 5000K Color Temp.	RB - Remote Battery SRK - Surface Mounting Kit SUK - Suspension Mounting Kit
ORDER INFO			
Not Applicable Example ^	MW	35K	

PROD	SOURCE	35K SPECS	40K SPECS	50K SPECS		
FPE2X4	L40.0	<ul style="list-style-type: none">35K - 3500K Color Temp5000 LED Delivered Lumens125 Lumens Per Watt80 CRI	<ul style="list-style-type: none">40K - 4000K Color Temp5100 LED Delivered Lumens127.5 Lumens Per Watt80 CRI	<ul style="list-style-type: none">50K - 5000K Color Temp5200 LED Delivered Lumens130 Lumens Per Watt80 CRI		
	L50.0	<ul style="list-style-type: none">35K - 3500K Color Temp6250 LED Delivered Lumens125 Lumens Per Watt80 CRI	<ul style="list-style-type: none">40K - 4000K Color Temp6375 LED Delivered Lumens127.5 Lumens Per Watt80 CRI	<ul style="list-style-type: none">50K - 5000K Color Temp6500 LED Delivered Lumens130 Lumens Per Watt80 CRI		

REPLACEMENT PART	PART NO	NOTES



TERONLIGHTING.COM
33 DONALD DR, FAIRFIELD, OH 45014
P: 513.858.6004 F: 513.858.6038
E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.